




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁶ : B24B 7/22, 9/06, B25B 27/00, B24B 41/04, B28D 1/30, B23Q 1/25</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/34954</p> <p>(43) International Publication Date: 15 July 1999 (15.07.99)</p>
<p>(21) International Application Number: PCT/CA99/00002</p> <p>(22) International Filing Date: 5 January 1999 (05.01.99)</p> <p>(30) Priority Data: 2,226,169 5 January 1998 (05.01.98) CA</p> <p>(71)(72) Applicant and Inventor: SACCON, Lorenzo [CA/CA]; 25 Gambello Crescent, Toronto, Ontario M3J 1W2 (CA).</p> <p>(74) Agents: JEFFREY, John, C. et al.; Suite 301, 133 Richmond Street West, Toronto, Ontario M5H 2L7 (CA).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>
<p>(54) Title: STONE TILE FINISHING SYSTEM</p> <p>(57) Abstract</p> <p>A stone tile finishing system (1) includes an apparatus and a group of different tools usable in the apparatus for various tile finishing operations. The apparatus itself has a motor (21), a tool mount rotated by the motor (21) and a tile support (37) movable relative to the motor (21). The tool mount has capacity to receive any one of the different tools. The motor (21) is swingably held within the apparatus by a height adjustable motor (21) mount (19) which enables moving of the motor (21) to different working positions relative to the tile (37) support for carrying out the various tile finishing operations.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

TITLE: STONE TILE FINISHING SYSTEMFIELD OF THE INVENTION

The present invention relates to a multi-
5 function stone tile finishing system.

BACKGROUND OF THE INVENTION

Numerous different finishing operations are
10 required when working with stone tiles. Some tiles
must be cut to different sizes than others. Some
tiles must have different edge finishes than others.
Also, some tiles must be drilled to provide through
passages. The tiles must then be completed in a
15 polishing operation.

According to conventional practice, a
plurality of different tool finishing apparatuses are
required to perform the above different operations.
20 If numerous different operations are required on a
single tile, then that tile must be moved from one
apparatus to another. Therefore, using known
technology, it is costly from both an equipment and a
time standpoint to provide different finishes to a
25 stone tile.

SUMMARY OF THE INVENTION

The present invention provides a stone tile
30 finishing system where various different tile
finishing operations can be carried out in a single
apparatus. That apparatus is usable with any one of a
number of different tools.

- 2 -

The apparatus itself comprises a housing containing a motor with a tool mount rotated by the motor and a tile support movable relative to the motor. The tool mount has capacity to receive any one
5 of the different tools and when in operation, a tool selected from the different tools is secured at the tool mount. The motor is swingably held in the apparatus by a height adjustable motor mount which enables moving of the motor to different working
10 positions relative to the tile support for carrying out the various tile finishing operations.

BRIEF DESCRIPTION OF THE DRAWINGS

15 The above as well as other advantages and features of the present invention will be described in greater detail according to the preferred embodiments of the present invention in which;

Figure 1 is a perspective view of an apparatus
20 used in a tile finishing system according to a preferred embodiment of the present invention;

Figure 2 is an enlarged exploded perspective view of the motor and motor mount used in the apparatus of Figure 1;

25 Figure 3 is an assembled side view of the motor mount of Figure 2 when used to perform a tile cutting operation;

Figure 4 is a view similar to Figure 3, but showing the apparatus used to perform a tile edge
30 finishing operation;

Figure 4A is a view similar to Figure 4 showing the apparatus used for a tile drilling operation;

Figure 5 is a perspective view of the
35 apparatus of Figure 1 in a storage position;

- 3 -

Figures 6 through 10 show tiles on which a number of different tile finishing operations have been performed using the tile finishing system of the present invention.

5

DETAILED DESCRIPTION ACCORDING TO THE PREFERRED
EMBODIMENTS OF THE PRESENT INVENTION

Figure 1 shows a tool finishing apparatus
10 generally indicated at 1. Figures 2 through 4 of the drawings show only some of the various different tools which are usable with the apparatus.

The apparatus itself comprises a main housing
15 3 supported in a working position by legs 5. Housing 3 includes recessed side handles 4.

A hood 6 is pivotally secured at 7 to the top
of the housing. A releasable lock 8 holds the hood in
20 the Figure 1 use position.

A motor mount to which a motor 21 is
adjustably secured is secured to the hood 6. This
motor mount comprises a main frame portion 9 and
25 movable frame portion 11.

Referring to Figure 2, it will be seen that
the main frame portion 9 of the motor mount has a
bottom seat 9a provided with a pair of openings 10.
30 The movable frame portion 11 includes a pair of legs
15 only one of which can be seen in Figure 2. These
two legs are slideably fitted into the openings 10 in
frame portion 9.

- 4 -

Frame portion 11 further includes a threaded opening 13 while frame portion 9 includes a threaded adjustment member 17. This adjustment member is rotated by a hand control 19 on the outer face of frame portion 9.

Figures 3 and 4 show that the frame portion 11 is adjusted in an up and down fashion relative to frame portion 9 by turning the handle 19 of threaded adjustment member 17. Posts 15 on frame portion 11 slide through the openings 10 in frame portion 9 to guide the movement of frame portion 11.

Motor 21 rotates a tool mount generally indicated at 23. This tool mount comprises a threaded center shaft 25 having a back plate 27. Figures 2 and 3 show a saw blade held at the tool mount. The inside face of the saw blade is held against plate 27 and secured in position by a bolt which threads into shaft 25.

Figure 3 shows the apparatus set up for a tile cutting operation. The motor mount carrying the motor is adjustable in a vertical direction as earlier described relative to a tile support 37 seen in Figure 1 of the drawings. This tile support on which a stone tile is placed is slideably held on a pair of guide rods 41. A tile positioning gauge 37 is provided on the top surface of the tile support. This gauge is adjustable to accurately move the tile to different positions relative to the motor.

A tile, when secured on support 37 is forced with sliding movement of the support to pass beneath the saw blade which is dropped down into a working

- 5 -

position by lowering motor mount 11 and motor 21. The height adjustment of the motor is controlled in very small increments according to the depth of the cut required in the tile. In some cases, the tile may be cut completely through and in other cases, the cut may only be partially through the tile. The threading on adjustment member 17 is sufficiently fine to allow very minute accurate adjustments of the height of the motor according to the desired cut.

10

A key feature of the present invention relates to the fact that motor 21 is swingably held on the motor mount. More particularly, the motor is secured by a swivel connection generally indicated at 29 to the motor mount. This swivel connection includes an adjustable release and tightening member as shown. This allows the motor to be swung from the Figure 3 to the Figure 4 position through a full 90° or any angle therebetween. A stop 12 prevents the motor from swinging through more than 90°.

15
20

As will be seen in Figure 3, shaft 23 is extending in a horizontal position whereas in Figure 4, the motor has been swung such that the shaft is now facing in a vertical direction. Figure 4 also shows a bullnozing tool rather than a saw fitted to the tool mount. This bullnozing tool is rotated in a horizontal plane to provide a tile edge finish as shown in Figure 10 rather than to provide a tile cutting operation as shown in Figure 6.

25
30

The bullnozing tool can be replaced by different types of edge finishing tools to provide other edge finishes. Figure 9 for example shows that

- 6 -

a different tool can be fitted to the tool mount to provide a rounded tile edge.

As earlier mentioned, motor 21 can be adjusted
5 to and secured at different angles between the Figure 3 and Figure 4 positions. For example, by rotating the motor through a 45° rather than a 90° angle and again using the saw blade, the tile can be provided with a mitered edge as shown in Figure 8 of the
10 drawings.

Figure 4a of the drawings show a drill bit 27 which is threaded directly into shaft 25. This bit is used to perform drilling operations on the tile as
15 shown in Figure 7 of the drawings. The drill bit can be replaced with a router to perform routing operations. These operations can be used to provide holes through the tile or finishes at the edge of the tile.

20 The apparatus includes a mounting system for the tile support which helps in a tile cutting operation. More particularly, the ends of the guides 41 for support 37 are adjustably seated on a track 43.
25 A tension spring 45 urges the guides to their normal working position. In this position, support 37 carrying the tile is pushed across the guides where the saw blade provides a cut in the tile. It may however be difficult to return the support plate
30 carrying the tile back to the starting position because of interference with the tile. The spring loading of the guides 41 allows the support plate carried by the guides to be manipulated to clear the tile.

35

- 7 -

The main body of housing 3 is provided with a lower water chamber 2. A pump operated flexible hose 31 draws water from the chamber and directs the water for cooling purposes at the tool in the tool mount. A
5 valve 35 controls the water flow through the hose. The water after being used to perform its cooling function drips back down into the main chamber of the housing where it is recycled for further use. The flexibility of the hose allows it to move up and down
10 with the motor.

Although only certain tools and finishing operations have been described above, it is to be appreciated that other tools can also be used for
15 performing further tile finishing operations.

From the description above, it will now be understood how numerous different tile finishing operations can be performed using a single relatively
20 compact apparatus. As a further feature, the apparatus itself can be converted from the use position of Figure 1 to a portable position as shown in Figure 5. In this position support plate 37 and legs 5 are removed and stored in the main chamber of
25 housing 3 after it has been drained. Lock member 8 is released and hood 6 is swung down such that the motor and the motor mount are also contained within the main chamber of the housing protected by the hood. The lock is then moved back into the locking position to
30 hold the hood closed relative to the housing. The housing is now easily carried by the handles 4 to any desired location.

Although various preferred embodiments of the
35 present invention have been described in detail, it

- 8 -

will be appreciated by those skilled in the art, that variations may be made without departing from the spirit of the invention or the scope of the appended claims.

- 9 -

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

- 5 1. A stone tile finishing system comprising an apparatus and a group of different tools usable in said apparatus for various tile finishing operations, said apparatus comprising a housing containing a motor, a tool mount rotated by said motor, said tool
10 mount having capacity to receive any one of said different tools, a tool selected from said group of different tools secured at said tool mount and a tile support movable relative to said tool mount, said motor being swingably held by a height adjustable
15 motor mount which enables moving of said motor to different working positions relative to said tile support for carrying out the various tile finishing operations.
- 20 2. A stone tile finishing apparatus which receives any one of numerous different finishing tools for various tile finishing operations, said apparatus comprising a housing, a motor within said housing, a tool mount rotated by said motor and having capacity
25 to receive numerous different tools, and a tile support movable relative to said tool mount, said motor being swingably connected to a height adjustable motor mount which enables both different height and angled settings of said motor relative to said tile
30 support for carrying out the various tile finishing operations.
3. A stone tile finishing apparatus as claimed in Claim 2, wherein said motor is secured to said motor
35 mount by a swivel connection having a releasable lock

- 10 -

which allows the different angled settings of said motor relative to said motor mount.

4. A stone tile finishing system as claimed in
5 Claim 3, wherein said motor is swingable through a 90° angle.
5. A stone tile finishing apparatus as claimed in
10 Claim 2, having a self contained water supply and a movable hose which is carried by said motor mount and which directs water from said water supply at said tool mount regardless of the height setting of said tool mount.
- 15 6. A stone tile finishing apparatus as claimed in Claim 2, wherein said motor mount holding said motor is supported on a movable portion of said housing, said movable portion holding said motor mount and motor in a working position exposed outwardly of said
20 housing and being movable to carry said motor mount and motor to a storage position inside of said housing.
- 25 7. A stone tile finishing apparatus as claimed in Claim 6, wherein said movable portion comprises a hood which covers said motor mount and motor in the storage position.
- 30 8. A stone tile finishing apparatus as claimed in Claim 2, wherein said tile support is held on a guide which is spring loaded to adjust positioning of said guide.





FIG. 1.

2/5

FIG. 2.



3 / 5

FIG. 3.






FIG. 4.



4/5



5/5

FIG.6.




FIG.7.




FIG.8.




FIG.9.




FIG.10.





FIG.5.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 99/00002

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B24B7/22 B24B9/06 B24B27/00 B24B41/04 B28D1/30
B23Q1/25

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B24B B28D B23Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 611 191 A (THIBAUT SA) 17 August 1994 see page 2, column 1, line 37 - page 2, column 2, line 42 ---	1-4
A	DE 32 43 218 A (WASSMER PAUL) 24 May 1984 see page 7, paragraph 5 - page 8, paragraph 1 ---	1,2,8
A	FR 2 506 652 A (LGB BRICAUD) 3 December 1982 see page 1, line 11 - line 20 ---	1-4
A	US 5 681 211 A (WIAND RICHARD K) 28 October 1997 see column 2, line 65 - column 3, line 16 see column 10, line 52 - column 11, line 6 --- -/--	5

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

20 May 1999

Date of mailing of the international search report

31/05/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Eschbach, D

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 99/00002

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 4 772 160 A (BARWASSER GUENTER) 20 September 1988 see abstract</p> <p>-----</p>	6,7

INTERNATIONAL SEARCH REPORT

information on patent family members

Inte: onal Application No

PCT/CA 99/00002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0611191 A	17-08-1994	FR 2701228 A	12-08-1994
DE 3243218 A	24-05-1984	NONE	
FR 2506652 A	03-12-1982	NONE	
US 5681211 A	28-10-1997	US 5586928 A	24-12-1996
		US 5549509 A	27-08-1996
		DE 19546228 A	01-08-1996
		DE 19524697 A	08-02-1996
US 4772160 A	20-09-1988	DE 8613032 U	14-08-1986
		EP 0245726 A	19-11-1987
		JP 62292354 A	19-12-1987